<Hydrobox (Reversible)>

Model name				ERPX-VM2E	ERPX-YM9E
		Type		Heating and cooling	Heating and cooling
		Expansion vessel		✓	✓
		Booster heater		✓	✓
Dimensions		H×W×D	mm	800 × 530 × 360	800 × 530 × 360
Weight (empty)			kg	31	33
Control board power supply (Phase / V / Hz)				~/N, 230, 50 Hz	~/N, 230, 50 Hz
Heater	Booster heater	Power supply (Phase / V / Hz)		~/N, 230, 50 Hz	3~, 400, 50 Hz
		Capacity	kW	2	3+6
		Current	A	9	13
		Breaker	A	16	16
Guaranteed operating range *1	Indoor unit ambient		°C	0~35°C (≤80%RH)	0~35°C (≤80%RH)
	Outdoor	Heating	°C	See outdoor unit spec table.	See outdoor unit spec table.
		Cooling	°C	See outdoor unit spec table.*2	See outdoor unit spec table.*2
Target temperature range	Heating	Room temperature	°C	10~30	10~30
		Flow temperature *3	°C	20~75	20~75
	Cooling	Room temperature	°C	—	—
		Flow temperature	°C	5~25	5~25
Sound power level (PWL)			dB(A)	40	40

*1 The environment must be frost-free.
*2 During cooling operation at low outdoor temperature (10°C or lower), frozen water may cause damage on plate heat exchanger.
*3 Max temperature is depending on the connected outdoor unit.