

Specifications

MODEL			PFFY-P20VEM-E	PFFY-P25VEM-E	PFFY-P32VEM-E	PFFY-P40VEM-E	PFFY-P50VEM-E	PFFY-P63VEM-E
Power source	1-phase 220-230-240 V 50/60 Hz							
Cooling capacity (Nominal) ^{*1}	kW	2.2	2.8	3.6	4.5	5.6	7.1	
	Btu/h	7500	9600	12300	15400	19100	24200	
Heating capacity (Nominal) ^{*2}	kW	2.5	3.2	4.0	5.0	6.3	8.0	
	Btu/h	8500	10900	13600	17100	21500	27300	
Power input	Cooling kW	0.021	0.026	0.031	0.037	0.054	0.061	
	Heating kW	0.021	0.026	0.031	0.037	0.054	0.061	
Current input	Cooling A	0.26-0.25-0.24	0.31-0.30-0.29	0.37-0.35-0.34	0.39-0.38-0.36	0.58-0.56-0.55	0.52-0.50-0.48	
	Heating A	0.26-0.25-0.24	0.31-0.30-0.29	0.37-0.35-0.34	0.39-0.38-0.36	0.58-0.56-0.55	0.52-0.50-0.48	
External finish	Galvanized steel plate, MUNSELL (1.0Y 9.2/0.2)/ABS, MUNSELL (5.32GY 8.75/0.37)							
External dimension H x W x D ^{*3}	mm	669(726)x1142x217	669(726)x1142x217	669(726)x1142x217	669(726)x1342x217	669(726)x1342x217	669(726)x1542x217	
Net weight	kg	29.5	29.5	30	35	35	39.5	
Heat exchanger	Cross fin (Aluminum fin and copper tube)							
FAN	Type x Quantity	Sirocco fan x 2	Sirocco fan x 2	Sirocco fan x 2	Sirocco fan x 3	Sirocco fan x 3	Sirocco fan x 4	
	Air flow rate	m ³ /min	5.0 - 6.0 - 7.0	5.5 - 6.5 - 8.0	5.5 - 7.0 - 8.5	8.0 - 9.5 - 11.0	10.0 - 11.5 - 13.5	12.0 - 14.0 - 16.5
		l/s	83 - 100 - 117	92 - 108 - 133	92 - 117 - 142	133 - 158 - 183	167 - 192 - 225	200 - 233 - 275
	cfm	177 - 212 - 247	194 - 230 - 282	194 - 247 - 300	282 - 335 - 388	353 - 406 - 477	424 - 494 - 583	
External static press.	Pa	0	0	0	0	0	0	
Motor	Type	DC motor						
	Output kW	0.096						
Air filter	PP honeycomb fabric.							
Refrigerant piping diameter	Gas (R410)	mm	12.7 (1/2) Brazed	12.7 (1/2) Brazed	12.7 (1/2) Brazed	12.7 (1/2) Brazed	12.7 (1/2) Brazed	15.88 (5/8) Brazed
	Liquid (R410)	mm	6.35 (1/4) Brazed	6.35 (1/4) Brazed	6.35 (1/4) Brazed	6.35 (1/4) Brazed	6.35 (1/4) Brazed	9.52 (3/8) Brazed
Field drain pipe size	O.D.32 (1-1/4)							
Sound pressure level	dB(A)	23.0-27.0-31.0	25.0-29.0-34.0	25.0-31.0-36.0	29.0-33.0-36.0	34.0-37.0-41.0	32.0-36.0-40.0	

1. Nominal cooling conditions

Indoor: 27° CD.B./19° CW.B. (81° FD.B./66° FW.B.), Outdoor: 35° CD.B. (95° FD.B.), Pipe length: 7.5 m (24-9/16 ft.), Level difference: 0 m (0 ft.)

2. Nominal heating conditions

Indoor: 20° CD.B. (68° FD.B.), Outdoor: 7° CD.B./6° CW.B. (45° FD.B./43° FW.B.), Pipe length: 7.5 m (24-9/16 ft.), Level difference: 0 m (0 ft.)

3. The values in () show the height of unit with leg.

* Details on foundation work, duct work, insulation work, electrical wiring, power source switch, and other items shall be referred to the Installation Manual.

* Due to continuing improvement, above specifications may be subject to change without notice.